

SEAMLESS MOBILITY WITH EXCEPTIONAL PERFORMANCE

3인치 POS용 영수증 프린터 SRP-350plusIII



주요특징



프리미엄급 프린팅 성능

- 최고 300mm/sec 인쇄속도 (SRP-350 II 대비 20% 속도 향상)
- 축소인쇄 기능지원 (소모품 비용절감 가능)
- 16단계의 그레이 스케일 그래픽 인쇄
- 스테디셀러인 SRP-350 라인의 신제품



최상의 호환성 및 유연성

- iOS, 안드로이드, 윈도우 RT 8.1 등 스마트 기기와 호환가능 (MFi 인증)
- 와이파이 혹은 블루투스 무선 인쇄 지원 (옵션 선택)
- USB와 Ethernet 기본 제공

사용자 중심의 디자인

- 용지 걸림 방지 가이드(Anti-jam)
- 벽걸이형으로 공간 절약 가능
- 2인치, 3인치 용지 선택



3인치 POS용 영수증 프린터

SRP-350plusIII



제품사양

Print Characteristics	
Print Method	Direct Thermal
Print Speed	SRP-350plusIII: 300 mm/sec / SRP-352plusIII: 270 mm/sec
Print Resolution	SRP-350plusIII: 180 dpi / SRP-352plusIII: 203 dpi
Print Width	Up to 72 mm
Sensor	Paper End, Paper Near End, Cover Open
Media Characteristics	
Media Type	Receipt
Media Width	80 mm / 58 mm
Media Roll Diameter	Up to 83 mm
Media Thickness	0.062 ~ 0.075 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (WxLxD)	145 x 200 x 146 mm (5.70 x 7.87 x 5.74 inch)
Weight	1.56 kg (3.43 lbs)
Power	EnergyStar Certified, External Power Adaptor 100-240V AV, 50/60Hz
Drawer Port	2 ports (via y-type adaptor)
Performance Characteristics	
Memory	64 Mbit SDRAM, 32 Mbit FlashROM
NV Image Memory	768 Kbytes (mono)
Receive Buffer	4 Kbytes
User Define Buffer	12 Kbytes
Interface	Triple Interface : USB V2.0 FS + Ethernet + Serial / Parallel / WLAN* / Bluetooth V2.1+ EDR** / powered USB * WLAN: 802.11b/g/n **Bluetooth: Class 1 (100 m), MFI certified
Environment Characteristics	
Temperature	Operating: 0 ~ 45°C (32 ~ 113°F) / Storage: -20 ~ 60°C (-4 ~ 140°F)
Humidity	Operating: 10 ~ 80% RH / Storage: 10 ~ 90% RH
Reliability	
Printer Unit (MCBF)	70 Million Lines
Thermal Print Head (TPH)	150 km
Auto Cutter	1.8 Million Cuts
Software	
Emulation	BXL / POS
Driver / Utility	Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program
SDK	iOS SDK, Android SDK, Windows SDK
Fonts / Graphics / Symbologies	
Character Size	Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24 KOR, CHN, JPN: 24 x 24
Characters Per Line	SRP-350plusIII: Font A: 42 Font B, C: 56 KOR, CHN, JPN: 21 / SRP-352plusIII: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 / Extended Graphics: 128 x 37 page / International: 32
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code

BR-SRP-350plusIII-KR-APR14-V1

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

BIXOLON®

www.bixolon.com



BIXOLON Co., Ltd.

경기도 성남시 분당구 판교역로241번길
20 (삼평동) 7~8층 463-400

Tel (031) 218 5500

Fax (031) 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de